

**RESIDENTIAL POST FRAME**

UP TO 20 FEET WIDE

Roof Covering - Shingle/Steel

Roof Deck - 1/2" OSB (Shingle)/2 x 4 (Steel)

Truss Or Rafter Ties May Be Required

Trusses: Yes X or No X

\*\*If no see rafter information below\*\*

Truss/Rafter Block Size: 2 x 6

Rafter Size: 2 x 8

Rafter Spacing: 2 foot on center

Ridge Size: 2 x 10

Ceiling Joist Size: 2 x 6

Ceiling Joist Spacing: 2 foot on center

Pole Size: 4 x 6

Pole Spacing: 8 feet

Ceiling Height: Up to 10 feet

Roof Peak Height: 24 foot in AF, AG or R-1 zoning  
20 feet in all other zones.

Insulation Materials: \_\_\_\_\_

Finish Materials: \_\_\_\_\_

Carrier Size - Two 2 x 8

Wall Purlins - 2 x 4

Type of Siding - Vinyl/Steel

Skirt Board Size - Two 2 x 6 or 1 2 x 10

Concrete Slab Floor Thickness - 4 inches

All Concrete Footings Shall Be Mixed With  
Clean Water Outside Of The Hole.

Depth Below Grade - 48 inches to bottom  
of hole

Footing Height - 6 inches

\*\*One 80 pound bag of Redi Mix  
Concrete will equal 6 inches of  
concrete\*\*

Footing Width - 14 inches

